查询1MBH75D-060供应商

SPECIFICATION

(TENTATIVE)

Device Name : IGBT

Type Name : 1MBH75D-060S

Spec. No. : MS5F 4623

Date : June-21-1999

This material and the information herein is the prop
Fuji Electric Co.,Ltd. They shall be neither reproduced,
lent, or disclosed in any way whatsoever for the use
third party nor used for the manufacturing purposes
the express written consent of Fuji Electric Co.,Ltd

Fuji Electric Co.,Ltd.
Matsumoto Factory

	DATE	NAME	APPROVED
DRAWN	June-21-'99	K. Kawada	T. HOSEN
CHECKED	Jun-21-'99	T. HOSEN	

Fuji Electric Co.,Ltd.

DWG. NO. MS5F 4623 1/13

1MBH75D-060S

1. Outline Drawing



CONNECTION

① GATE
② COLLECTOR
③ EMITTER

2. Equivalent circuit



3. Absolute maximum ratings (Tc=25°C)

Items			Symbols	Ratings	Units
Collector-Emitter Voltage			V_{CES}	600	V
Gate-Emitter Voltage			V_{GES}	±30	V
Collector Current	DC	Tc=25 °C	Ic_{25}	82	A
		Tc=100°C	Ic_{100}	75	A
	1ms	Tc=25 °C	Icp	225	A
IGBT Max. Power Dissipation			Pc	310	W
FWD Max. Power Dissipation			Pc	180	W
Operating Temperature			Tj	+ 150	°C
Storage Temperature			Tstg	-40 ~ +150	°C
Mounting Screw Torque			——	70	N·cm

4. Electrical Characteristics (at Tc=25°C unless otherwise specified)

Items		Symbols	Characteristics			Conditions	Unit
			min.	typ.	max.		
Zero gate voltage Collector Current		I_{CES}	—	—	1.0	V_{GE} = 0V V_{CE} = 600V	mA
Gate-Emitter leakage Current		I_{GES}	—	—	10	V_{CE} = 0V V_{GE} = ±30V	μA
Gate-Emitter Threshold Voltage		$V_{GE(th)}$	4.0	5.0	6.0	V_{CE} = 20V Ic = 75mA	V
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	—	2.4	2.9	V_{GE} = 15V Ic = 75A	V
Input capacitance		Cies	—	3700	—	V_{GE} = 0V	pF
Output capacitance		Coes	—	350	—	V_{CE} = 25V	
Reverse transfer capacitance		Cres	—	190	—	f = 1MHz	
Switching Time	Turn-on time	ton ※	—	0.15	—	Vcc = 300V Ic = 75A V_{GE} = ±15V R_G = 24 Ω (Half Bridge) Inductance Load	μs
		tr ※	—	0.09	—		
		trr2	—	0.03	—		
	Turn-off time	toff	—	0.50	0.62		
		tf	—	0.10	0.17		
	Turn-on time	ton ※	—	0.15	—	Vcc = 300V Ic = 75A V_{GE} = +15V R_G = 6.0Ω (Half Bridge) Inductance Load	
		tr ※	—	0.09	—		
		trr2	—	0.03	—		
	Turn-off time	toff	—	0.50	0.62		
		tf	—	0.10	0.17		
FWD forward voltage		VF	—	2.0	2.5	IF=75A, VGE=0V	
Reverse recovery time		trr	—	0.06	0.10	IF=75A, VGE=-10V VR=300V, dv/dt=100A/μs	μs

※ Turn-on characteristics iclude trr2. Seee figure.A in next page.

5. Thermal resistance characteristics

Items	Symbols	Characteristics			Conditions	Unit
		min.	typ.	max.		
Thermal resistance	Rth(j-c)	——	——	0.40	IGBT	°C/W
	Rth(j-c)	——	——	0.69	FWD	

6. Switching waveform



Collector Current vs. Collector-Emitter Voltage
Tj=25℃



Collector Current vs. Collector-Emitter Voltage
Tj=125℃



This material and the information herein is the property of Fuji Electric Co.,Ltd.,They shall be neither reproduced, copied, or disclosed in any way whatsoever for the use of third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Collector-Emitter Voltage vs Gate-Emitter Voltage
Tj=25°C



Collector-Emitter Voltage vs Gate-Emitter Voltage
Tj=125°C



This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Switching time vs Collector current
Vcc=300V, RG=6Ω, VGE=+15V, Tj=125°C



Switching time vs Collector current
Vcc=300V, RG=24Ω, VGE=±15V, Tj=125°C



This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Switching time vs RG
Vcc=300V, Ic=75A, VGE=+15V, Tj=125°C



Switching time vs RG
Vcc=300V, Ic=75A, VGE=±15V, Tj=125°C



This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Dynamic input characteristics

Tj=25℃



Capacitance vs. Collector-Emitter Voltage

Tj=25℃



This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

1MBH75D-060S

Reverse Biased Safe Operating Area

RG=6Ω, +VGE≦30V, -VGE=15V, Tj≦125°C



1MBH75D-060S

Forward Bias Safe Operating Area



This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Reverse recovery time vs. Forward current
VR=300V, -di/dt=100A/μsec



Reverse recovery current vs. Forward current
VR=300V, -di/dt=100A/μsec



This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Forward Voltage vs. Forward current



Reverse recovery chracteristics vs. -di/dt
VR=300V, IF=75A, Tj=125℃





This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.